

NFPA 1850 PPE CABINET DRYERS



NFPA 1850 COMPLIANCE: CRITICAL REQUIREMENTS

- 100% MADE IN THE USA.
- NFPA 1850 COMPLIANT.
- GUARANTEED PPE PROTECTION.
- PER NFPA 1850 GUIDELINES, PPE MUST NOT RE DRIED AT TEMPERATURES EXCEEDING 120°F. OUR CABINETS PREVENT DESTRUCTIVE OVERHEATING.

MODEL FDC-2G: COMPACT SERVICEABILITY

SPECIFICATIONS

- INTERIOR CAPACITY: 17.5 CUBIC FT.
- ELECTRICAL: 110-120V 60HZ 15 AMP BREAKER.
- EXTREME END-USER SERVICEABILITY: SIMPLIFIED DESIGN FOR IMMEDIATE FIELD MAINTENANCE AND PARTS REPLACEMENT.



MODEL 2201-6: HIGH-CAPACITY EFFICIENCY

SPECIFICATIONS

- MASSIVE INTERIOR CAPACITY: 63 CUBIC FT.
- OUTLET AIRFLOW: 460 CFM.
- ELECTRICAL: 208-220/240V 60HZ 40 AMP BREAKER.
- BUILT IN FLOOR DRAIN FOR IMMEDIATE CONDENSATE REMOVAL.
- STANDARD 5-YEAR WARRANTY.
- OUTFITTED WITH:
 - 4 COAT HANGERS,
 - 13-PAIR GLOVE RACK,
 - 2 BOOT HANGERS.























— TOXIC —
SUPPRESSION™



— TOXIC —
SUPPRESSION™

PPE CABINET DRYERS

PRODUCT SPECIFICATIONS & OVERVIEW

Categories & Data		2-Gear PPE Drying Cabinet Model FDC-2G	6-Gear / Hose & Gear PPE Drying Cabinet Model 2201
Exterior Construction & Finish	Products		
Physical Construction	Material	Heavy-Duty Steel Construction, Powder-Coated Finish	
	Country of Origin	Made in USA	
Physical Dimensions	Exterior Dimensions (HxWsD)	 67.5" x 23.5" x 24.5"	 72" x 55" x 31"
	Net Weight	150 Lbs	460 Lbs
	Shipping Weight	 225 Lbs	 630 Lbs
Hanging & Storage Components (Standard included)	Interior Capacity	17.5 Cubic Ft	63 Cubic Feet
	Total Shelf Area	7.5 Sq. Ft (3 shelves x 2.5 Sq. Ft each)	(Large multi-purpose interior)
	 Coat Hangers	4 Stainless Steel Hangers	4 Gear Hangers 
	 Glove Rack/Hanger	Horizontally-mounted Door Brackets	1 Glove Rack (holds 26 gloves) 
	 Boot Hanger	Horizontally-mounted Door Brackets	2 Boot Hangers (holds 12 boots) 
Additional Hangers/Accessories (Multi-purpose)	Door-Mounted Hanging Brackets	Optional Multi-purpose Hanger, Hose Drying Shelf	
Airflow & Ventilation	Design	Insulated, Dual Walls	High-Efficiency Drying
	Fan Airflow 		460 cfm
	Exhaust/Vent 	Insulated Design 	6" Diameter Exhaust, accepts 4" ducting 
Temperature & Control System 	Interface		
	User Settings		
	NFPA Temperature Alignment	Total of 5 presets (Air Only, 120°F)	5 selectable settings: Air Only, Low (120°F), Medium, Normal, High
	Operable Range	Designed for gear safety.	Wide operation range for versatile use.
	Cycle Time	Optimized for delicate gear.	Full range Air Only to High operation.
	LED Indicators	Associated LED Light Indicators for presets	
	LCD Display	Time Remaining Display, Revealed Temperature on Display	
Features & Maintenance 	Construction	NFPA 1850 Guidelines Followed	Conforms to NFPA 1850 guidelines
	Insulation	Yes	
	Built-in Drain	Built-in floor drain	
	Serviceability	Designed for easy maintenance and repair by end-user	
	Locking Mechanism	-	Flush-mounted, lockable slam latch
	Voltage	110-120V 60 Hz 15 Amp	208-220/240V 60 Hz 1 Phase 40 Amp
	Warranty	Generic hanging brackets	5 Year Warranty